

Machinelijst VDL Systems – Afdeling Verspaning



AFKORTEN		
Halfautomatische verstek-afkortmachine		Dimensions (mm)
Jaespa 265	1x (2016)	Max. H=260
Jaespa 240GT	1x (2007)	Max. H=240
EMMESI 450M	1x (1994)	Max. H=130
Halfautomatische cirkelzaagmachine		Dimensions (mm)
Kaltenbach KKS400	1x (1976)	Max. H=110; Max. L=6000
Volautomatische afkortmachine		Dimensions (mm)
MEGA H330 GA	1x (2016)	Max. H=330; Max. B=350

DRAAIEN					
CNC-draaibank		Doorlaat (mm)	Lengte	RPM	Diameter
Doosan Puma 3100LY	1x (2015)	103	1280	3000; sub: 5000	420
Doosan Lynx 220LM	1x (2011)	51	510	6000	320
Doosan Puma 2100M (incl. BMO Robotbelader Pt24F)	1x (2010) 1x (2016)	68	520	4500; sub: 5000	406
Victor V-turn 26-2	1x (2000)	75	500	3500	300
CNC-draaibank met subspindel en stafafvoer		Doorlaat (mm)	Lengte	RPM	Diameter
Victor V-turn 26/110	1x (2004)	75	900	3500; sub: 4500	300
Conventionele draaibank		Doorlaat (mm)	Lengte	Diameter	
STX Maxturn 2160	1x (1990)	78	1500	300	

FREZEN					
CNC-freesbank		Verplaatsing (XYZ)		Bed	RPM
Hedelius C60/2500	1x (2011)	2500;620;520		3000x600	12000
Hedelius C80/3200	1x (2007)	3200;810;550		4000x750	12000
Doosan Mynx NM510	1x (2007)	1020;510;600		1200x500	12000
Victor V-center 125	1x (2000)	1250;600;610		1400x550	6000
Conventionele freesbank horizontaal		Verplaatsing (XYZ)		RPM	
TOS F2V	1x (1993)	590;400;300		2000	
TOS FNGJ32	1x (1995)	745;250;320		4000	

BOREN EN TAPPEN					
Coördinaten-boorstraat CN-gestuurd		Verplaatsing (XYZ)		RPM	
CMA TRD CN 40	1x (2009)	4500;600;400		Spindel: 3000; boor: 5000	
Tapmachine handmatig		Min. dimensie		Max. dimensie	
Roscamat tapboor elektrisch	1x (2013)	M3		M30	
Roscamat tapboor perslucht	1x (2006)	M3		M12	
Roscamat tapboor perslucht	1x (1999)	M3		M30	